Handwashing and Water storage Unit	Samples	Quality & safety
JERRYCAN, rigid, 20L, food grade plastic, screw cap 50mm with 20mm threaded tap heat sunk into base (Yellow colour)		Tap seal must be tested for watertightness. Evidence of method of adaptation and safe production if PVC melting is involved.
JERRYCAN, rigid, 20L, food grade plastic, screw cap 50mm without tap (handwashing for wastewater) with lid security ratchet intact – Yellow colour	Front - View Side - View	
Rectangular handwashing PVC basin (10L capacity): length 300mm, width 270mm, depth 150mm with 50mm diameter hole cut (drill with hole-cutter) to right central base of basin (sufficient space to allow attachment of standard length drainage waste pipe and rubber washer (see picture pictures) -	50mm to allow 40mm diameter wastewater fitting	Note that a hole 40mm or smaller will cause fracture when fitting is installed.
Note: Drainage pipe will be 40mm diameter aperture and should fit without forcing –ensure drainage pipe comes with rubber wash – see picture)	sufficient clearance from curvature of basin base to ensure flush fitting of wastewater rubber washer to underside	
Paper clips (Big sized) 100 pieces per pack		

KIT, CORDLESS DRILL, 14V, (preferably BOSCH –see picture. But similar durability if BOSCH is too expensive) with bits (including 5mm Brad point drill – vanadium steel)	
Soldering Iron with cable (for plastic seal repairs)	
3mm diameter Multi- Purpose Polypropylene Rope	92 yards/ roll
Activated carbon filter masks.	
GLASSES, clear rigid plastic, eyes front + sides protection	