ELECTRICAL DRAWING

ELECTRICAL LEGEND

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	1x20W FLOURECENT WTH DIFFUSER		2 GANG 2 WAY SWITCH
	1x15W CEILING MOUNTED FITTING		T.P.N. DISTRIBUTION BOARD
Ф	1x15W WALL BRACKET FITTING	•	4x25W CHANDERLIER CEILING FITTING
H	1x15W EXTERNAL LIGHT FITTING	<u> </u>	1x15 AMP SOCKET OUTLET
⅓ H	FIRE ALARM SIREN	<u> </u>	1X13 AMP SOCKET OUTLET
©	32W EXTERNAL LIGHT ON POLES	818	4500 COOKER CONTROL UNIT
٨	120W 1.4M CEILING FAN	➾	3000W WATER HEATER POINTS
\odot	SMOKE EXTRACTOR		TELEPHONE OUTLETS
1	3 GANG 1 WAY SWITCH	+	TELEVISION AERIAL OUTLET
1	1 GANG 1 WAY SWITCH	LK	LIGHTING KIOSK
	BED SWITCH	*	ELCB
0	1 x 15W BOWL FITTING	8=	2x13AMP SOCKETS OUTLET
	2 x 40W FLOURESCENT		FIRE ALARM PANEL
0	10W ENERGY SAVING BULBS	∅	10W ENERGY SAVING REFLECTIVE MULTI COLORED SPOT LIGHT
¥	125W EXTENAL LIGHTING ON 3M POLE STAND	÷	200W EXTENAL LIGHTING ON 5M POLE STAND
	250W WATER PROOF LIGHT FITTING	\otimes	SMOKE ALARM DETECTOR

Notes

ELECTRICAL NOTES:

All electrical works to be done in accordance with these drawings and the general specifications for electrical instalations works according to IEE regulations

Wiring shall be full concealed conduit via P.V.C conduit pipes of 20mm Ø

Cable shall be PVC insulated armoured and non armoured (copper conductors)

All 5A switches and ceiling fan regulators shall be wired and


mounted at the height of 1.4m above finished floor level

All 13A SSO shall be wired in ring circuit and mounted at 0.40m above finished floor level Good earthing system must be ensured by burying 1.2m earth electrode for the eleb boards

PROPOSED POULTRY HOUSE DEVELOPMENT

ELECTRICAL DRAWING





DESIGNED BY ·	ABDULLAHI	SHEET NO
CHECK BY	ENGR.ISHAYA DAVID	1
PHONE NO	07030683526	

